



Non-vac model



Self generated dust collection model



Central dust collection model



JET  Accessories



905310
6" PSA TYPE



905317
6" PSA VACUUM TYPE

RANDOM ORBITAL SANDERS

6" DUAL ACTION Heavy Duty DA63NV (403212)

- Compact and light weight dual action sander designed for single hand operation
- Popular non-vacuum model
- Dual action provides a swirl free finish
- Paddle throttle and vinyl lined top housing for operator comfort and control
- Heavy duty manaliium cylinder, steel front end plate and heat treated through out for extended service life
- Muffled, rear exhaust outlet directs exhaust air away from the work piece
- Adjustable speed regulator

Standard Accessories: 6" PSA sanding pad (905310), Wrench

6" DUAL ACTION Heavy Duty DA63SG (403214)

- Self generated dust collection system for work place safety, includes crush resistant hose and reusable dust collection bag
- Same features as above

Standard Accessories: Crush resistant hose, Reusable collection bag, 6" PSA 6 hole sanding pad (905317), Wrench



DA63SG Self generated dust collection system

6" DUAL ACTION Heavy Duty DA63CV (403217)

- Equipped for use with a central dust collection system for work place safety
- Same features as above

Standard Accessories: 6" PSA 6 hole sanding pad (905317), Wrench

MOD. NO. PROD. NO.	DA63NV 403212	DA63SG 403214	DA63CV 403217
Stroke (Orbit Dia.)	3/16"	3/16"	3/16"
Spindle Thread	5/16" - 24	5/16" - 24	5/16" - 24
Free Speed R.P.M./S.P.M.	10,000	10,000	10,000
Overall Length	6-3/4"	9-1/2"	8-1/4"
Weight (Lbs.)	2.2	2.3	2.3
Avg. Air Consumption (CFM)	10	10	10
Min. Hose Size	3/8"	3/8"	3/8"
Air Inlet Thread	1/4"	1/4"	1/4"

• FOR MAXIMUM PERFORMANCE WE RECOMMEND 90 LB PSI AIR PRESSURE

RANDOM ORBITAL SANDERS



6" DUAL ACTION Standard Duty FS127A (403203)

- 3/16" diameter stroke for swirl free finish
- Maximum 10,000 R.P.M. is adjustable by use of built-in regulator
- Ball bearing construction for long life
- Dynamically balanced for minimum vibration
- Die-cast aluminum housing with black rubber cover for protection
- Ideal for feather edging, metal preparation and finish work on body filler
- Rated at 86 decibels

Standard Accessories: 6" sanding pad (905310)

Optional Accessories: 5" sanding pad (905313)



6" DUAL ACTION "QUIET" Heavy Duty FS127Q (403201)

- Improved muffler design reduces noise level in the work place
- Dual sanding action for swirl free finish and fast stock removal, combines an 11/64" orbital stroke and 10,000 R.P.M. free speed rotary action
- Design improvements for greater durability
- Ball bearing construction for long life
- Dynamically balanced for minimum vibration
- Throttle lock to prevent accidental start up
- Ideal for feather edging, metal preparation and finish work on body filler
- Rated at 83.8 decibels

Standard Accessories: 6" sanding pad (905310)



6" DUAL ACTION Professional Duty DA65SG (403215)

- Powerful air motor, heavy duty aluminum housing and full size handle make this sander ideal for professional use
- Provides dual action sanding for a swirl free finish
- Ball bearing construction for long service life
- Self generated dust collection system for work place safety, includes hose and reusable dust collection bag
- Double walled dust shroud with insert for improved dust collection capability
- Infinitely adjustable speed regulator
- Vinyl housing cover to prevent marring of the work piece
- Ergonomic, full sized, handle with vinyl cover for operator comfort and control
- Muffled, rear exhaust outlet directs exhaust air away from the work piece

Standard Accessories: Reusable dust bag and hose, 6" PSA 6 hole sanding pad (905317), Wrench



DA65SG Self generated dust collection system

8" DUAL ACTION Heavy Duty DA85NV (403221)

- Heavy duty gear driven system provides increased torque for fast stock removal on large surface areas - ideal for bondo busting
- Dual action provides a swirl free finish
- Vinyl cover on housing prevents marring of the work piece
- Infinitely adjustable speed control
- Ergonomic handle with vinyl cover and finger guard for operator comfort and safety
- Toggle release paddle throttle prevents accidental starts
- Ball bearing construction for long service life

Standard Accessories: 8" PSA sanding pad (905316)



MOD. NO. PROD. NO.	FS127A 403203	FS127Q 403201	DA65SG 403215	DA85NV 403221
Stroke (Orbit Dia.)	3/16"	11/64"	3/8"	5/32"
Spindle Thread	5/16"-24	5/16"-24	5/16"-24	N/A
Free Speed R.P.M./S.P.M.	10,000	10,000	10,000	900
Overall Length	8-3/4"	9-1/2"	10"	11-1/2"
Weight (Lbs.)	4.25	4.25	4	5.2
Avg. Air Consumption(CFM)	4	4	18	16
Min. Hose Size	3/8"	3/8"	3/8"	3/8"
Air Inlet NPT	1/4"	1/4"	1/4"	1/4"

• FOR MAXIMUM PERFORMANCE WE RECOMMEND 90 LB PSI AIR PRESSURE

905-814-6859 - 1-866-517-3289 - www.marcur.com



NEW!



JET Accessories



RESIN FIBRE SANDING DISCS

4" to 7" aluminum oxide discs are the standard of the metalworking industry and the most popular discs used for general metal removal. Please consult our abrasives catalogue for specifications.

SANDERS/POLISHERS

5" HIGH SPEED SANDER

VS125A (403102)

- An excellent economical high speed sander
- Complete with 3", 4-1/2" and 5" backing plates
- Deluxe grip handle for comfortable operation
- Built-in power regulator
- Excellent for a variety of surface conditioning operations such as paint removal, light touch-up work, rust removal, etc.

Standard Accessories: 3" Backing plate (905301), 4-1/2" Backing plate (905302) and 5" Backing plate (905303); Holding tool (905304), Nut (905305)

7" ANGLE SANDER - PROFESSIONAL DUTY

AS700HD (403109)

- Heavy duty construction for professional use
- Hardened, precision ground spiral beveled gears for long life & low vibration
- Insulated handle cover, contoured throttle lever and rear exhaust for operator comfort
- Side handle mounts on either side
- Excellent for heavy rust removal, metal sanding and contour work

Standard Accessories: Pad (905306), Nut (905307), Side Handle, Wrenches

7" VERTICAL SANDER

VS700C (403112)

- Double idler planetary gear system
- Ball bearing construction
- Built-in grease fitting for grease refill
- Light-weight and 2 handle design offers maximum operator control
- 4500 R.P.M. is ideal for rust removal and general sanding

Standard Accessories: Plastic pad (905306), Nut (905307), Side handle, Wrenches

7" VERTICAL POLISHER

VP700C (403117)

- Double idler planetary gear reduction increases tool life
- Ball bearing construction for vibration free operation and longer tool life
- Built-in power and speed control
- Light-weight
- 2000 R.P.M. is ideal for buffing and polishing paint, metal, wood or plastic

Standard Accessories: Rubber pad (905308), Nut (905309), Side handle, Wrenches

MOD. NO. PROD. NO.	VS125A 403102	AS700HD 403109	VS700C 403112	VP700C 403117
Backing Disc Size	3" - 5"	7"	7"	7"
Spindle Size	7/16" - 20	5/8" - 11NC	5/8" - 11NC	5/8" - 11NC
Free Speed R.P.M.	18,000	4,500	4,500	2,000
Overall Length	6"	15-1/2"	7-1/4" *	7-1/4" *
Weight (Lbs.)	2.5	6	5.5	6
Avg. Air Consumption (CFM)	6	13	6	5.5
Min. Hose Size	3/8"	3/8"	3/8"	3/8"
Air Inlet NPT	1/4"	1/4"	1/4"	1/4"

*Height

• FOR MAXIMUM PERFORMANCE WE RECOMMEND 90 LB PSI AIR PRESSURE

SANDERS




ORBITAL SANDER Standard Duty OS232 (403303)

- Compact palm-grip design allows one hand operation
- Dynamically balanced for minimum vibration
- Built-in regulator for positive speed control
- All ball bearing construction
- Ideal for finishing furniture and auto body repair
- Orbital action helps deliver a patternless finish

Standard Accessory: Pad assembly (905311)

Uses 3-3/4" x 9" abrasive strips



ORBITAL SANDER Professional Duty OS37SG (403307)

- Heavy duty orbital sander with 3-2/3" x 7" pad, designed for professional use
- Front and rear handle design permits two handed operation for maximum comfort and control
- Self generated dust collection system for work place safety, includes hose and reusable dust collection bag
- Ball bearing construction for long service life
- Infinitely adjustable speed regulator
- Ergonomically shaped, full sized, handle with vinyl cover for operator comfort and control
- Muffled, rear exhaust outlet directs exhaust air away from the work piece
- Orbital sanding action helps deliver a pattern free finish

Standard Accessories: Reusable dust bag and hose, 3-2/3" x 7" PSA sanding pad (905315)

Optional Accessory: 3-2/3" x 7" hook and loop pad (905314)



OS37SG Self generated dust collection system

DUAL PISTON STRAIGHT LINE SANDER BFS315D (403313)

- Deluxe two-piston body file
- Front and rear piston ride on needle bearings for precise, smooth performance
- Well-balanced design
- Easy-to-grip two handle design for maximum control
- High quality aluminum pad
- Ideal for body filing, shaping and levelling large flat surfaces

Standard Accessory: Pad assembly (905312)



Uses 2-3/4" x 17-1/2" abrasive strips

MOD. NO.	OS232	OS37SG	BFS315D
PROD. NO.	403303	403307	403313
Stroke	3/16"	3/16"	1"
Free Speed S.P.M.	7,000	7,000	2,200
Overall Length	6-3/4"	9-1/2"	16"
Weight (Lbs.)	4.4	4.6	6.25
Avg. Air Consumption (CFM)	6	20	8
Min. Hose Size	3/8"	3/8"	3/8"
Air Inlet NPT	1/4"	1/4"	1/4"

• FOR MAXIMUM PERFORMANCE WE RECOMMEND 90 LB PSI AIR PRESSURE

