



Features Jacobs Chuck



Features Machined Steel Industrial Quality Keyed Chuck

NEW!



Features Jacobs Chuck



Features Machined Steel Industrial Quality Keyed Chuck

NEW!



3/8" (905753), 1/2" (905754)
Keyless Chuck



3/8" (905755), 1/2" (905756)
Industrial Keyed Chuck

DRILLS

3/8" REVERSIBLE Standard Duty ADX380R (404415)

- Hardened steel planetary gears for long life performance
- Excellent power to weight ratio
- Forward/Reverse switch conveniently located for one handed operation
- Contoured handle design and aluminum die cast throttle offer precise operator control
- Excellent for a wide range of drilling jobs

3/8" REVERSIBLE Heavy Duty - with keyed chuck ADR380HD (404412)

- Designed for heavy duty use this powerful yet compact air drill features a heat treated ductile cylinder, two steel motor bearing plates, black oxide finished rotor and full cage planetary gear mechanism for maximum service life
 - Reverse valve situated for fast and easy one handed operation
 - Includes heavy duty precision machined all steel keyed chuck (905755)
 - Complete with black rubber insulating grip for operator comfort and safety (Prod. No. 905751)
 - Pressure grease fitting on housing permits easy maintenance for longer tool life
 - Air inlet screen prevents solid matter from entering the tool for extended tool life
- Standard Accessory:** Industrial keyed chuck (905755)
Optional Accessory: Keyless chuck (905753)

1/2" Standard Duty RDX12 (404423)

- Double reduction planetary gear system gives low speed and high torque for heavier drilling jobs
- Ball and needle bearing construction
- Auxiliary side handle included
- This 500 R.P.M. 1/2" air drill is designed for heavier steel plate drilling, cylinder honing and all jobs requiring high torque

1/2" REVERSIBLE Heavy Duty - with keyed chuck ADR12HD (404422)

- Heavy duty motor with double reduction planetary gear system to 800 R.P.M. provides exceptional power
 - Reverse valve situated for fast and easy one handed operation
 - Includes heavy duty precision machined all steel keyed chuck (905756)
 - Side handle provides maximum operator control and absorbs stall torque reaction for operator safety
 - Complete with black rubber insulating grip for operator comfort and safety (Prod. No. 905752)
 - Ball and needle bearing construction
 - Air inlet screen prevents solid matter from entering the tool, extends tool life
- Standard Accessory:** Industrial keyed chuck (905756)
Optional Accessory: Keyless chuck (905754)

MOD. NO.	ADX380R	ADR380HD	RDX12	ADR12HD
PROD. NO.	404415	404412	404423	404422

Chuck Capacity	3/8"	3/8"	1/2"	1/2"
Reversible	Yes	Yes	No	Yes
Horsepower	.33	.50	.40	.40
Spindle Size	3/8" - 24	3/8" - 24	3/8" - 24	3/8" - 24
Free Speed R.P.M.	2,200	1,800	500	800
Overall Length	6-3/4"	7.5"	9-3/4"	9-1/2"
Weight (Lbs.)	2.75	2.70	3.74	4.8
Avg. Air Consumption (CFM)	4	4	3	4
Min. Hose Size	3/8"	3/8"	3/8"	3/8"
Air Inlet NPT	1/4"	1/4"	1/4"	1/4"

• FOR MAXIMUM PERFORMANCE WE RECOMMEND 90 LB PSI AIR PRESSURE

DRILLS



3/8" REVERSIBLE ANGLE HEAD Heavy Duty AD38AHR (404418)

- Exceptionally low profile 90° angle head design makes this drill ideal for working in confined areas
- Reverse valve for improved efficiency
- Lubrication port on the gear head permits convenient preventative maintenance resulting in extended tool life
- Rear exhaust outlet directs exhausted air away from the workplace for operator comfort and safety
- Teasing throttle delivers improved control from start up through run down
- Specifically designed for corner drilling, holesaw use, auto body work and other general applications



Features Jacobs Chuck

PISTOL GRIP SCREWDRIVER PSD14H (404606)

- Reversible screwdriver with internally adjusted clutch
 - Three interchangeable clutch springs for maximum variety of torque settings
 - Pistol grip design with handle exhaust outlet for operator comfort
 - Quick release 1/4" hex bit holder
 - Variable torque settings make this tool ideal for use in all industrial applications
- Standard Accessories:** 3 clutch springs (905761), 2 wrenches



TIRE BUFFER ATB716 (403152)

- Designed for tire patching, roughing and cleaning applications
 - Features 7/16" hex quick change chuck for quick tooling changes
 - Paddle throttle with toggle lock to prevent accidental starts
 - Rear exhaust directs exhaust air away from the work piece for cleaner work place
 - Teasing throttle allows operator to match tool RPM to application
- Standard Accessories:** 7/16" hex by 3/8"-24NF mandrel (overall length: 1-7/8", threaded portion: 9/16") (905771)
- Optional Accessory:** Exhaust hose kit (905481)



Exhaust Hose Kit (905481)

MOD. NO. PROD. NO.	AD38AHR 404418	PSD14H 404606	ATB716 403152
Chuck Capacity	3/8"	1/4" Hex	7/16" Hex
Torque Rating (In - Lbs.)		44-115	
Reversible	Yes	Yes	No
Horsepower	.33	.35	.5
Spindle Size	3/8" - 24	—	—
Free Speed R.P.M.	1,700	1,800	2,500
Overall Length	8-1/4"	8-1/2"	9"
Weight (Lbs.)	2.42	2.7	2
Avg. Air Consumption (CFM)	4	4	10
Min. Hose Size	3/8"	3/8"	3/8"
Air Inlet NPT	1/4"	1/4"	1/4"

• FOR MAXIMUM PERFORMANCE WE RECOMMEND 90 LB PSI AIR PRESSURE

JET Accessories



570142

JET-KUT™ Gold
SUPER PREMIUM 135° SPLIT POINT DRILL BITS