



HOSE REELS

SPRING REWIND Heavy Duty

- All body and frame components made of superior heavy gauge steel for professional applications/installations — **Check & Compare!**
 - All metal parts powder coated for corrosion free performance
 - Reinforced L-shaped base
 - Professional super duty spring mechanism for long life — **Check & Compare!**
 - Nine position, adjustable guide arm
 - Heavy duty four direction, non snag rollers — **Check & Compare!**
 - Anti lock-out ratchet mechanism prevents reel from locking up when hose is fully extended
 - Heavy duty American made, solid brass swivel fitting — **Check & Compare!**
 - Can be wall, floor or ceiling mounted
- Standard Accessories:** Hose and fittings



391721 3/8" x 25' Air/Water



391722 3/8" x 50' Air/Water



391726 1/2" x 50' Air/Water

MOD. NO. PROD. NO.	AW3825 391721	AW3850 391722	AW1250 391726
-----------------------	------------------	------------------	------------------

Hose Diameter (I.D.)	3/8"	3/8"	1/2"
Hose Length	25'	50'	50'
Hose Inlet/Outlet (N.P.T.)	3/8"	3/8"	1/2"
Max. Hose Pressure (PS.I.)	300	300	300
Max. Temperature (C)	100°	100°	100°
Max. Temperature (F)	210°	210°	210°
Unit Weight (Lb.)	29	54	59
Intended Use	Air/Water	Air/Water	Air/Water

MOD. NO. PROD. NO.	0A1450 391746	01250 391747	G1450 391731
-----------------------	------------------	-----------------	-----------------

Hose Diameter (I.D.)	1/4"	1/2"	1/4"
Hose Length	50'	50'	50'
Hose Inlet/Outlet (N.P.T.)	1/4"	1/2"	1/4"
Max. Hose Pressure (PS.I.)	300	2,000	5,000
Max. Temperature (C)	—	100°	100°
Max. Temperature (F)	—	210°	210°
Unit Weight (Lb.)	53	64	53
Intended Use	Oxy/ Acetylene	Oil	Grease

NOTE:

There are many similar looking air/water rewind hose reels in the market. However, these industrial quality JET reels offer heavier gauge body and frame steel components, superior American made air swivel fittings, an extra heavy duty spring mechanism (tested to 30,000 cycles) and a superior quality four direction snag roller system — **Check & Compare!**

Reels rated at maximum 300 PSI are furnished with rubber hose.

Reels rated at maximum 2,000 PSI are furnished with S.A.E. 100 R1 AT one wire braid hose.

Reels rated at maximum 5,000 PSI are furnished with S.A.E. 100 R2 AT two wire braid hose.



391746 Oxy/Acetylene



391747 2,000 PSI Oil



391731 5,000 PSI Grease

HOSE REELS/ACCESSORIES



HAND CRANK HOSE REELS


- Provide the ideal method for safe & economic handling of air and water hose
- Heavy duty steel drum and frame construction
- Corrosion resistant powder coating
- Spring tensioned brake prevents free wheeling
- Solid brass swivel and fittings
- Model HC200 features brass and stainless steel fluid path
- Mount on floor, bench or service truck

MOD.NO PROD. NO.	HC100 391741	HC200 391742
Hose Diameter (I.D.)	3/8"	3/8"
Maximum Hose Length	100'	100'
Hose Inlet/Outlet (N.P.T.)	3/8"	3/8"
Maximum Hose Pressure (P.S.I.)	300	300
Unit Weight (Lb.)	13	14
Intended Use	Air/Water	Air/Water

(Note: Hose not included)



391741



391742

CEILING & FLOOR MOUNT Swivel Base SRCF (391739)

- 360° swivel base, universal

WALL MOUNT Pivot Base SRW808 (391730)

- 140° pivot base for AW3850, AW1250, OA1450, O1250 & G1450

WALL MOUNT Pivot Base SRW809 (391729)

- 140° pivot base for AW3825



391739



391729, 391730

RECOIL AIR HOSES

APU1425 (408122) 1/4" x 25'

APU3825 (408127) 3/8" x 25'

- Light, versatile, easy to handle and difficult to kink polyurethane construction
- Stores in 1/30 of working length
- 1/4" rated at: 90-100 PSI (working), 200 PSI (burst)
- 3/8" rated at: 90-100 PSI (working), 250 PSI (burst)
- 360° swivel ends, 1/4" NPT, male
- Bright orange for high visibility
- The most efficient system of storing and using air hose



PVC AIR HOSES

AH2538R (408104) 3/8" x 25'

AH5038R (408105) 3/8" x 50'

- PVC air hose stays pliable in cold weather, use in temperatures ranging from -26° to +65° C
- Tough abrasion and oil resistant outer surface
- Cover is pin pricked for safety. If air seeps between layers pin holes allow it to escape, preventing sudden failure
- 300 lbs. per square inch working pressure
- 1/4" NPT fittings are applied using hydraulic pressure to ensure a perfect seal and no damage to the hose under the fitting



BLOW GUN

AG16 (409902)

- 1/4" N.P.T. air inlet
- Extra nozzle included
- Ideal for all air cleaning jobs

